


XBee® & XBee-PRO® ZB

ZigBee® Embedded RF Modules for OEMs

XBee and XBee-PRO ZB embedded RF modules deliver low-cost, low-power wireless connectivity using the ZigBee PRO Feature Set.



Overview


XBee and XBee-PRO ZB embedded RF modules provide wireless connectivity to end-point devices in ZigBee mesh networks. Utilizing the ZigBee PRO Feature Set, these modules are interoperable with other ZigBee devices, including devices from other vendors*. XBee users can have their ZigBee network up-and-running in a matter of minutes, without configuration or additional development.

XBee modules are ideal for low-power, low-cost applications. XBee-PRO modules are power-amplified, extended-range versions of XBee modules. Products in the XBee family are easy to use, share a common hardware footprint, and are interoperable with other XBee products. Available in a variety of protocols for different applications, one XBee can be substituted for another with minimal development time and risk.

Digi's unsurpassed offering of Drop-in Networking products provides seamless communication between devices. XBee adapters provide wireless connectivity to devices in wired networks. XBee wall routers extend the range and strength of a ZigBee network. ConnectPort™ X gateways enable users to access remote devices in a network.

*Interoperability requires the ZigBee Feature Set or ZigBee PRO Feature Set to be deployed on all devices. Contact Digi Support for details.


Application Highlight




Features/Benefits

- Interoperability with ZigBee devices from other vendors*
- No configuration needed for out-of-the-box RF communications
- Advanced configuration options available via simple AT or API commands
- Common XBee footprint for a variety of RF modules
- Outdoor RF line-of-sight range up to 1 mile (1.6 km)
- Programmable XBee-PRO ZB offers foolproof customization or application development
- ZigBee mesh networking protocol
 - Improved data traffic management
 - Remote firmware updates
 - Self-healing and discovery for network stability

Related Products



Gateways



Modules



Adapters



Development Kits



Network Extenders



Sensors



Performance

RF Data Rate	250 Kbps	
Indoor/Urban Range	133 ft (40 m)	300 ft (90 m)
Outdoor/RF Line-of-Sight Range	400 ft (120 m)	2 miles (3200 m) / Int'l 5000 ft (1500 m)
Transmit Power	1.25 mW (+1 dBm) / 2 mW (+3 dBm) boost mode	63 mW (+18 dBm) / Int'l 10 mW (+10 dBm)
Receiver Sensitivity (1% PER)	-96 dBm in boost mode	-102 dBm

Features

Adjustable Power	Yes	
Serial Data Interface	3.3V CMOS UART	
Configuration Method	API or AT commands, local or over-the-air	
Frequency Band	2.4 GHz	
Interference Immunity	DSSS (Direct Sequence Spread Spectrum)	
Serial Data Rate	1200 bps - 1 Mbps	
ADC Inputs	(4) 10-bit ADC inputs	
Digital I/O	10	
Antenna Options	Chip, Wire Whip, U.FL, RPSMA	PCB Embedded Antenna, Wire Whip, U.FL, RPSMA
Programmability	No	Yes

Networking & Security




Encryption	128-bit AES	
Reliable Packet Delivery	Retries/Acknowledgments	
IDs and Channels	PAN ID, 64-bit IEEE MAC, 16 channels	PAN ID, 64-bit IEEE MAC, 15 channels

Power Requirements

Supply Voltage	2.1 - 3.6VDC	2.7 - 3.6VDC
Transmit Current	35 mA / 45 mA boost mode @ 3.3VDC	205 mA, up to 220 mA with programmable variant
Receive Current	38 mA / 40 mA boost mode @ 3.3VDC	47 mA, up to 62 mA with programmable variant
Power-Down Current	<1 uA @ 25° C	3.5 uA, 4 uA @ 25° C with programmable variant

Regulatory Approvals

FCC (USA)	Yes	
IC (Canada)	Yes	
ETSI (Europe)	Yes	
C-TICK (Australia)	Yes	
TELEC (Japan)	Yes	Yes (int'l unit only)



Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support



91001471
C3/410

BUY ONLINE • www.digi.com

Delmation Products BV
info@delmation.nl
www.delmation.nl
Tel: +31 (0)79 342 2041

